

SEMIFUSE® SFS1812F PTC Fuses

The SFS1812F series of PTC fuses is our mid-size SMD range. The high ratings allow engineers to replace radial PTCs with SMD solutions in numerous electronics applications. This footprint can handle currents up to 3A and voltages up to 60V.

Characteristics


Agency Approvals; UL, CSA & TÜV

Part Number	I_{hold} (A)	I_{trip} (A)	V_{max} (dc)	I_{max} (A)	P_{max} (W)	Maximum time to trip @ 23°C		Resistance @ 23°C		Maximum Dimension (mm)	
						Current (A)	Time (s)	R_{min} (Ω)	R_{1max} (Ω)	A	B
SFS1812F010TF	0.10	0.30	60	10	0.8	8.0	0.02	1.600	15.00	4.73	3.41
SFS1812F014TF	0.14	0.30	60	10	0.8	8.0	0.01	1.200	6.500	4.73	3.41
SFS1812F020TF	0.20	0.40	30	10	0.8	8.0	0.02	0.800	5.000	4.73	3.41
SFS1812F035TF	0.35	0.70	16	40	0.8	8.0	0.10	0.320	1.500	4.73	3.41
SFS1812F050TF	0.50	1.00	16	40	0.8	8.0	0.15	0.150	1.000	4.73	3.41
SFS1812F075TF	0.75	1.50	33	40	1.0	8.0	0.20	0.110	0.400	4.73	3.41
SFS1812F110TF	1.10	2.20	24	100	1.0	8.0	0.50	0.060	0.200	4.73	3.41
SFS1812F125TF	1.25	2.50	6	40	0.8	8.0	0.40	0.050	0.140	4.73	3.41
SFS1812F150TF	1.50	3.00	24	100	1.0	8.0	1.50	0.040	0.120	4.73	3.41
SFS1812F160TF	1.60	3.20	16	100	1.0	8.0	1.00	0.030	0.100	4.73	3.41
SFS1812F200TF	2.00	3.50	8	100	1.0	8.0	2.00	0.020	0.070	4.73	3.41
SFS1812F260TF	2.60	5.00	16	100	1.3	8.0	5.00	0.015	0.050	4.73	3.41
SFS1812F300TF	3.00	5.00	6	100	1.0	8.0	4.00	0.012	0.040	4.73	3.41

Definitions


- I_{hold} = Hold current - maximum current PTC will pass without tripping in 23°C still air
- I_{trip} = Trip current - minimum current at which the PTC will trip in 23°C still air
- V_{max} = Maximum voltage PTC can withstand without damage at rated current (I_{max})
- I_{max} = Maximum fault current PTC can withstand without damage at rated voltage (V_{max})

Thermal De-rating Curve



Configuration

SFS1812F Dimensions



Solder Pad Layout

